

S계열

표준규격	O-RING 사이즈				표준규격	O-RING 사이즈			
	T/오차범위		I.D/오차범위			T/오차범위		I.D/오차범위	
*S-2	1.5		1.5	±0.15	S-53	2		52.5	±0.25
S-3			2.5		S-55			54.5	
S-4			3.5		S-56			55.5	
S-5			4.5		S-60			59.5	
S-6			5.5		S-63			62.5	
S-7			6.5		S-65			64.5	
S-8			7.5		S-67			66.5	
S-9			8.5		S-70			69.5	
S-10			9.5		S-71			70.5	±0.40
S-11.2			10.7		S-75			74.5	
S-12			11.5		S-80			79.5	
S-12.5			12		S-85			84.5	
S-14			13.5		S-90			89.5	
S-15			14.5		S-95			94.5	
S-16			15.5		S-100			99.5	
S-18			17.5		S-105			104.5	
S-20			19.5		S-110			109.5	
S-22			21.5		S-112			111.5	
S-22.4	2	±0.10	21.9	S-115	114.5	±0.60			
S-24			23.5	S-120	119.5				
S-25			24.5	S-125	124.5				
S-26			25.5	S-130	129.5				
S-28			27.5	S-132	131.5				
S-29			28.5	S-135	134.5				
S-30			29.5	S-140	139.5				
S-31.5			31	S-145	144.5				
S-32			31.5	S-150	149.5				
S-34			33.5	*S-155	154.5				
S-35			34.5	*S-160	159.5				
S-35.5			35	*S-165	164.5				
S-36			35.5	*S-170	169.5				
S-38			37.5	*S-175	174.5				
S-39			38.5	*S-180	179.5				
S-40			39.5	*S-185	184.5	±0.80			
S-42			41.5	*S-190	189.5				
S-44			43.5	*S-195	194.5				
S-45	44.5	*S-200	199.5						
S-46	45.5	*S-205	204.5						
S-48	47.5	*S-210	209.5						
S-50	49.5	*S-215	214.5						

S계열

표준규격	O-RING 사이즈			
	T/오차범위		I.D/오차범위	
*S-220	2	±0.10	219.5	±0.80
*S-225			224.5	
*S-230			229.5	
*S-235			234.5	
*S-240			239.5	
*S-245			244.5	
*S-250			249.5	
*S-255			254.5	
*S-260			259.5	
*S-265			264.5	
*S-270			269.5	
*S-275			274.5	
*S-280			279.5	
*S-285			284.5	
*S-290			289.5	
*S-295			294.5	
*S-300			299.5	