

P계열

표준규격	O-RING 사이즈				표준규격	O-RING 사이즈			
	T/오차범위		I.D/오차범위			T/오차범위		I.D/오차범위	
P-2	1.9	±0.08	1.8	±0.14	P-40	3.5	±0.1	39.7	±0.37
P-3			2.8		P-41			40.7	±0.38
P-4			3.8		P-42			41.7	±0.39
P-5			4.8	±0.15	P-44			43.7	±0.41
P-6			5.8		P-45			44.7	
P-7			6.8	±0.16	P-46			45.7	±0.42
P-8			7.8		P-48			47.7	±0.44
P-9			8.8	±0.17	P-49			48.7	±0.45
P-10			9.8		P-50			49.7	
P-10A			2.4		±0.09			9.8	P-48A
P-11	10.8	±0.18		P-50A		49.6	±0.45		
P-11.2	11			P-52		51.6	±0.47		
P-12	11.8	±0.19		P-53		52.6	±0.48		
P-12.5	12.3			P-55		54.6	±0.49		
P-14	13.8			P-56		55.6	±0.50		
P-15	14.8	±0.20		P-58		57.6	±0.52		
P-16	15.8			P-60		59.6	±0.53		
P-18	17.8	±0.21		P-62		61.6	±0.55		
P-20	19.8	±0.22		P-63		62.6	±0.56		
P-21	20.8	±0.23		P-65		64.6	±0.57		
P-22	21.8	±0.24		P-67		66.6	±0.59		
P-22A	21.7			P-70		69.6	±0.61		
P-22.4	22.1			P-71		70.6	±0.62		
P-24	23.7		P-75	74.6	±0.65				
P-25	3.5	±0.1	24.7	±0.25	P-80	5.7	±0.13	79.6	±0.69
P-25.5			25.2		P-85			84.6	±0.73
P-26			25.7	±0.26	P-90			89.6	±0.77
P-28			27.7	±0.28	P-95			94.6	±0.81
P-29			28.7	±0.29	P-100			99.6	±0.84
P-29.5			29.2		P-102			101.6	±0.85
P-30			29.7		P-105			104.6	±0.87
P-31			30.7	±0.30	P-110			109.6	±0.91
P-31.5			31.2	±0.31	P-112			111.6	±0.92
P-32			31.7		P-115			114.6	±0.94
P-34			33.7	±0.33	P-120			119.6	±0.98
P-35			34.7	±0.34	P-125			124.6	±1.01
P-35.5			35.2		P-130			129.6	±1.05
P-36			35.7		P-132			131.6	±1.06
P-38			37.7	±0.37	P-135			134.6	±1.09
P-39			38.7		P-140			139.6	±1.12

P계열

표준규격	O-RING 사이즈				표준규격	O-RING 사이즈			
	T/오차범위		I.D/오차범위			T/오차범위		I.D/오차범위	
P-145	5.7	±0.13	144.6	±1.16	P-335	8.4	±0.15	334.5	±2.42
P-150			149.6	±1.19	P-340			339.5	±2.45
P-150A			149.5		*P-345			344.5	±2.48
P-155	8.4	±0.15	154.5	±1.23	*P-350			349.5	±2.51
P-160			159.5	±1.26	P-355			354.5	±2.54
P-165			164.5	±1.30	P-360			359.5	±2.57
P-170			169.5	±1.33	*P-365			364.5	±2.60
P-175			174.5	±1.37	*P-370			369.5	±2.63
P-180			179.5	±1.40	P-375			374.5	±2.67
P-185			184.5	±1.44	*P-380			379.5	±2.70
P-190			189.5	±1.48	P-385			384.5	±2.73
P-195			194.5	±1.51	*P-390			389.5	±2.77
P-200			199.5	±1.55	*P-395			394.5	±2.79
P-205			204.5	±1.58	P-400			399.5	±2.82
P-209			208.5	±1.61	*P-405			404.5	±3.00
P-210			209.5	±1.62	*P-410			409.5	
P-215			214.5	±1.65	*P-415			414.5	
P-220			219.5	±1.68	*P-420			419.5	
P-225			224.5	±1.71	*P-425			424.5	
P-230			229.5	±1.75	*P-430			429.5	
P-235			234.5	±1.78	*P-435			434.5	
P-240			239.5	±1.81	*P-440			439.5	±3.30
P-245			244.5	±1.84	*P-445			444.5	
P-250			249.5	±1.88	*P-450			449.5	
P-255			254.5	±1.91	*P-455			454.5	
P-260			259.5	±1.94	*P-460			459.5	
P-265			264.5	±1.97	*P-465			464.5	
P-270			269.5	±2.01	*P-470			469.5	
P-275			274.5	±2.04	*P-475			474.5	
P-280			279.5	±2.07	*P-480			479.5	
P-285			284.5	±2.10	*P-485			484.5	
P-290			289.5	±2.14	*P-490			489.5	±3.70
P-295			294.5	±2.17	*P-495			494.5	
P-300			299.5	±2.20	*P-500			499.5	
*P-305			304.5	±2.24	*P-505			504.5	
*P-310			309.5	±2.27	*P-510			509.5	
P-315			314.5	±2.30	*P-515			514.5	
P-320			319.5	±2.33	*P-520			519.5	
*P-325			324.5	±2.36	*P-525			524.5	±3.70
*P-330			329.5	±2.39	*P-530			529.5	

P계열

표준규격	O-RING 사이즈				표준규격	O-RING 사이즈			
	T/오차범위		I.D/오차범위			T/오차범위		I.D/오차범위	
*P-535	8.4	±0.15	534.5	±3.70	*P-870	8.4	±0.20	869.5	±6.00
*P-540			539.5		*P-880			879.5	
*P-545			544.5		*P-890			889.5	
*P-550			549.5		*P-900			899.5	
*P-555			554.5	±4.00	*P-910			909.5	±6.70
*P-560			559.5		*P-920			919.5	
*P-565			564.5		*P-930			929.5	
*P-570			569.5		*P-940			939.5	
*P-575			574.5		*P-950			949.5	
*P-580			579.5		*P-960			959.5	
*P-585			584.5		*P-970			969.5	
*P-590			589.5		*P-980			979.5	
*P-595			594.5		*P-990			989.5	
*P-600			599.5		*P-1000			999.5	
*P-610		±0.20	609.5	±4.70	*P-1020			1019.5	±7.5
*P-620			619.5		*P-1040			1039.5	
*P-630			629.5		*P-1060			1059.5	
*P-640			639.5		*P-1080			1079.5	
*P-650			649.5		*P-1100			1099.5	
*P-660			659.5		*P-1120			1119.5	
*P-670			669.5		*P-1140			1139.5	
*P-680			679.5		*P-1160			1159.5	
*P-690			689.5		*P-1180			1179.5	
*P-700			699.5		*P-1200			1199.5	
*P-710			709.5	±5.30	*P-1220			1219.5	
*P-720			719.5		*P-1240			1239.5	
*P-730			729.5		*P-1260			1259.5	
*P-740			739.5		*P-1280			1279.5	
*P-750			749.5		*P-1300			1299.5	
*P-760			759.5		*P-1320			1319.5	
*P-770			769.5		*P-1340			1339.5	
*P-780			779.5		*P-1360			1359.5	
*P-790			789.5		*P-1380			1379.5	
*P-800			799.5		*P-1400			1399.5	
*P-810			809.5	±6.00					
*P-820			819.5						
*P-830			829.5						
*P-840			839.5						
*P-850			849.5						
*P-860			859.5						