

V계열

표준규격	O-RING 사이즈				표준규격	O-RING 사이즈			
	T/오차범위		I.D/오차범위			T/오차범위		I.D/오차범위	
*V-10	4	±0.10	9.5	±0.20	*V-95	4	±0.10	94	±0.83
*V-11			10.5		V-100			99	
*V-12			11.5		*V-105			104	±0.97
*V-14			13.5		*V-110			109	
V-15			14.5		*V-115			114	
*V-16			15.5	±0.24	V-120			119	
*V-18			17.5		*V-125			124	±1.18
*V-20			19.5		*V-130			129	
*V-21			20.5		*V-135			134	
*V-22			21.5		*V-140			138.5	
V-24			23.5	*V-145	143.5				
*V-25			24.5	±0.33	V-150			148.5	±1.36
*V-26			25.5		*V-155			153	
*V-28			27.5		*V-160			158	
*V-30			29.5		*V-165			163	
*V-32			31.5		*V-170			168	
V-34			33.5	V-175	173			±1.53	
*V-35			34.5	*V-180	178				
*V-36			35.5	*V-185	183				
*V-38			37.5	*V-190	188				
V-40			39.5	*V-195	193				
*V-42			41.5	±0.49	*V-200			198	±1.70
*V-44			43.5		*V-205			203	
*V-45			44.5		*V-210			208	
*V-46			45.5		*V-215			213	
*V-48			47.5		*V-220			218	
*V-50			49.5	±0.61	V-225	6	±0.15	222.5	±1.95
*V-53			52.5		*V-230			227.5	
V-55			54.5		*V-235			232.5	
*V-56			55.5		*V-240			237.5	
*V-58			57.5		*V-245			242.5	
*V-60			59.5		*V-250			247.5	±2.20
*V-63			62.5		*V-255			252.5	
*V-65			64.5		*V-260			257.5	
*V-67			66.5		*V-265			262.5	
V-70			69		*V-270			267.5	
*V-75			74		V-275			272	±2.27
*V-80			79		*V-280			277	
V-85			84		*V-285			282	
*V-90			89		±0.83			*V-290	

V계열

표준규격	O-RING 사이즈				표준규격	O-RING 사이즈			
	T/오차범위		I.D/오차범위			T/오차범위		I.D/오차범위	
*V-295	6	±0.15	292	±2.27	*V-510	10	±0.30	504.5	±3.60
*V-300			297		*V-520			514.5	
*V-305			302	±2.34	V-530			524.5	
*V-310			307		*V-540			534	±3.92
*V-315			312		*V-550			544	
*V-320			317		*V-560			554	
V-325			321.5		*V-570			564	
*V-330			326.5	±2.51	*V-580			574	
*V-335			331.5		V585			579	
*V-340			336.5		*V-590			584	±4.24
*V-345			341.5		*V-600			593.5	
*V-350			346.5		*V-610			603.5	
*V-355			351.5	±2.68	*V-620			613.5	
*V-360			356.5		*V-630			623.5	
*V-365			361.5		*V-640			633.5	
*V-370			366.5		*V-650			643	±4.54
*V-375			371.5		*V-660			653	
V-380			376	*V-670	663				
*V-385			381	±2.83	*V-680			673	
*V-390			386		V-690			683	
*V-395			391		*V-700			692.3	±4.83
*V-400			396		*V-710			702.5	
*V-405			401		*V-720			712.5	
*V-410			406	±2.99	*V-730			722.5	
*V-415			411		V-740			732.5	
*V-420			416		*V-750			742	±5.12
*V-425			421		*V-760			752	
V-430			425.5		*V-770			762	
*V-435			430.5	±3.15	*V-780			772	
*V-440			435.5		V-790			782	
*V-445			440.5		*V-800			791.5	±5.44
*V-450			445.5		*V-810			801.5	
*V-455			450.5		±3.30			*V-820	
*V-460	455.5	*V-830	821.5						
*V-465	460.5	*V-840	831.5						
*V-470	465.5	V-845	836.5						
*V-475	470.5	*V-850	841.5	±6.06					
V-480	10	±0.30	475		±3.60			*V-860	851.5
*V-490			485					*V-870	861.5
*V-500			494.5					*V-880	871.5

V계열

표준규격	O-RING 사이즈			
	T/오차범위		I.D/오차범위	
*V-890	10	±0.30	881.5	±6.06
*V-900			891	
*V-910			901	
*V-920			911	
*V-930			921	
*V-940			931	
V-950			940.5	
*V-960			950.5	±6.67
*V-970			960.5	
*V-980			970.5	
*V-990			980.5	
*V-1000			990.5	
*V-1010			1000	
*V-1020			1010	
*V-1030			1020	
*V-1040			1030	
*V-1050			1039	
V-1055			1044	
*V-1100			1089	
*V-1150			1139	
*V-1200			1189	
*V-1250			1239	
*V-1300			1289	
*V-1350			1339	
*V-1400			1389	